## 1994 ASC Abstract

YBCO/Metal Oxide/YBCO Edge-Geometry Josephson Devices with Epitaxial Insulator Overlayers for High-Temperature Superconductive Electronics.\* J.B. BARNER, B.D. HUNT, M.C. FOOTE, and R.P. VASQUEZ, Jet Propulsion Laboratory, Pasadena, CA USA--We have been fabricating epitaxial edge-geometry Superconductor-Normal-Superconductor (SNS) Josephson devices using superconducting YBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-x</sub> (YBCO) and various normal metal oxides, deposited by pulsed-laser deposition. We begin our junction fabrication by depositing a bilayer Our edges are defined by an angled ion YBCO/Sr<sub>2</sub>AlTaO<sub>6</sub>(SAT). mill (-600 from normal) to produce a tapered YBCO/SAT edge using patterned metal milling masks, The milling times and film thicknesses are chosen to erode the metal milling mask prior to exposing the The growth of the N-layer and the YBCO counter YBCO film. electrode are done after the mill, in situ. Initial results with Nb milling masks and PrBa<sub>2</sub>Cu<sub>3</sub>O<sub>7-x</sub> are promising with, devices displaying current-voltage characteristics consistent with the resistively-shunted junction model. Additional results using various metal oxides, such as Pr and Co-doped YBCO, other milling mask materials and cross-over test circuits will be presented.

\*Work supported by NRL, NASA, and BMDO.

Presort Category: E-4

Registrant: Jeffrey B. Barner

Correspondence Author:: Jeffrey B. Barrier

Jet Propulsion Laboratory

M/S 302-231

California Institute of Technology

4800 Oak Grove Drive Pasadena, CA 91109

Tel: (81 8) 354-7353 Fax: (81 8) 393-4540

E-mail: JBarner@VAXEB.JPL.NASA.GOV

Preference: Oral

I, the registrant for this paper, am willing to review papers in the following subcategories: E-4, E-3, E-5, E-6, E-7, M-1,